

# HFU-EB25I

## 2.5" USB 2.0/FireWire Mobile Disk



### Key Features:

- Shock absorber, firm and elegant aluminum housing.
- Supports USB2.0/FireWire/1394/i-Link dual interfaces.
- Supports high-speed data transfer rates.
- Supports Bus powered, no external power supply required.
- Provides self-powered DC jack for hi-capacity or hi-current hard drive.
- Supports plug-and-play, no driver, no jumper pin or ID settings required.

### Specifications:

<b>Standards:</b>	USB1.1、USB2.0 and FireWire IEEE1394a Compliant
<b>Data Transfer Rate:</b>	USB Full-speed 12Mbps and high-speed 480Mbps. IEEE 1394a 400Mbps.
<b>Connectors:</b>	One mini USB B-type connector. One FireWire 6-pin connector. One 1.3 $\phi$ powered jack.
<b>Interface:</b>	USB/FireWire to 44 Pins IDE
<b>Indicators:</b>	One Green Read/Write active LED
<b>Power source:</b>	1. USB Bus power 2. FireWire Bus power 3. External AC power adapter. (DC5V/1A)
<b>Environmental:</b>	Operating Temperature:0 $^{\circ}$ C~40 $^{\circ}$ C Storage Temperature: -20 $^{\circ}$ C~60 $^{\circ}$ C Operating Humidity: 0%~80% RH, non-condensing
<b>Housing:</b>	Aluminum Case
<b>Unit Dimension:</b>	138*80* 15mm (L *W * H)
<b>Unit Weight:</b>	100g (without HDD)
<b>External Power Adapter:</b>	Output DC5V/1~1.5A (optional)
<b>Certification:</b>	FCC Class B, CE.
<b>System Support:</b>	Windows2000, XP. (*Windows 98 requires bundle driver.), VISTA Mac OS.8.6 or higher.



**HEISEI** Electronics Co. Ltd

Tel: 886-29152150 Fax: 886-29152849

<http://www.heisei.com.tw> E-mail:info@heisei.com.tw