



HHU-325AS USB 3.0 2.5" SATA HDD Enclosure

- Provides USB 3.0 interface compatible with prior ubiquitous USB 2.0 standard
- Support SuperSpeed, High-Speed and Full-Speed data transfer rate up to 5.0Gbps
- HDD turned off upon sleep/suspend/standby for green power management
- Anti-shock design to avoid damage of free body fall within 50 cm
- Complying with high speed BOT/UAS/UASP transmission of USB3.0
- Complying with SATA NCQ protocol
- Portable, light and handy, durability, flexibility, slim, compact and simple to use

Features

Electronic Specification

| | |
|--------------------------|---|
| HDD support | 2.5" SATAI/II HDD Capacity up to: 1 TB Height accepted: 9.5; 12.5 mm |
| Interface to PC | USB 3.0 |
| Interface to Device | SATAI / SATAII |
| Data Transfer Rate | USB3.0 up to 5.0Gbps Upstream: SuperSpeed, High-Speed, Full-Speed Downstream: SuperSpeed, High-Speed, Full-Speed, Low-Speed |
| Indicator | Red LED: Power Green LED: Access |
| Power Input | USB Bus Power or DC Jack |
| File backup | One Touch Backup (OTB) |
| System Environment | Operating Temperature: 5°C ~ 40°C Operating Humidity: 20%RH ~ 80%RH |
| Certification | FCC Class B, CE |
| System Support | Windows XP, Windows Vista 32/64, Windows 7 32/64 Mac OS 10.3.9 Linux Kernel 2.6.31 |
| OTB AP software / Driver | Windows XP, Windows Vista 32/64, Windows 7 32/64 |
| Driver / UASP | Compatible with NEC's UASP driver |

Mechanical Specification

| | |
|----------------------------|----------------------|
| Housing Material | Plastic and Aluminum |
| Board Dimensions (L*W*T) | 70*50*1 mm |
| Housing Dimensions (L*W*T) | 133*82*22 mm |
| Additional Function | Anti-shock |