



HHU-335AS USB 3.0 3.5" SATA HDD Enclosure

- Provides USB 3.0 interface compatible with prior ubiquitous USB 2.0 standard
- Support SuperSpeed, High-Speed and Full-Speed data transfer rate up to 5.0Gbps
- Complying with high speed BOT/UAS/UASP transmission of USB3.0
- Work with all USB 2.0 enabled computers and notebooks
- Complying with SATA NCQ protocol
- Aluminum case to avoid overheating. Compact and stylish design going with modern taste

Features

Electronic Specification

HDD support	3.5" SATA/II HDD Capacity up to: 2 TB Height accepted: 25.6 mm
Interface to PC	USB 3.0
Interface to Device	SATAI / SATAII
Data Transfer Rate	USB3.0 up to 5.0Gbps Upstream: SuperSpeed, High-Speed, Full-Speed Downstream: SuperSpeed, High-Speed, Full-Speed, Low-Speed
Indicator	Red LED: Power Green LED: Access
Power Input	DC Jack with power switch
File backup	One Touch Backup (OTB)
System Environment	Operating Temperature: 5°C ~ 40°C Operating Humidity: 20%RH ~ 80%RH
Certification	FCC Class B, CE
System Support	Windows XP, Windows Vista 32/64, Windows 7 32/64 Mac OS 10.3.9 Linux Kernel 2.6.31
OTB AP software / Driver	Windows XP, Windows Vista 32/64, Windows 7 32/64
Driver / UASP	Compatible with NEC's UASP driver

Mechanical Specification

Housing Material	Plastic and Aluminum
Board Dimensions (L*W*T)	108*35*1 mm
Housing Dimensions (L*W*T)	188*124.5*31 mm