

VIA PCI Host Card

Key Features:

- Provides USB2.0 interface fully backward compatibility with USB 1.1 devices.
- Compliant with EHCI and UHCI specifications.
- Supports high-speed data transfer rate up to 480Mbps.
- Supports hot swapping and Plug-and-Play capability.
- Supports low profile or standard's PCI slot.



Specifications:

	HU-202V
External Port:	2
Internal Port:	None
Dimension:	65*120 mm
Chipset:	VIA
Contact plating:	30 μ gold plate
Data Transfer Rate:	Supports high-speed 480Mbps / full-speed 12Mbps / low-speed 1.5Mbps
Output Voltage Per-port:	DC+5V
Output Current Per-port:	500mA
Environmental:	Operating Temperature:5 $^{\circ}$ C~40 $^{\circ}$ C Storage Temperature: -20 $^{\circ}$ C~60 $^{\circ}$ C Operating Humidity: 0%~80% RH, non-condensing
Certification:	FCC Class B, CE
System Support:	Windows [®] 98/SE, Windows [®] ME, Windows [®] 2000, Windows [®] XP, VISTA Mac [®] OS. 8.6 or higher
Ordering Information:	HU-202V 2-Port USB2.0 PCI Host Card HU-203V 3-Port USB2.0 PCI Host Card HU-204V 4-Port USB2.0 PCI Host Card HU-2041V 4-Port USB2.0 PCI Host Card (all external ports)