

SOHOUSB

It's simple, easy and faster!!

HAC-882JM

Magic Bridge II

Dual Interfaces Storage Bridge



Product Features:

- Solution for making storage device connection easier.
- Supports most types of ATA/ATAPI /SATA interface devices such as 2.5" HDD, 3.5" HDD and CD-ROM, CD R/W, DVD ROM and DVD R/W devices.
- Supports USB to IDE and SATA / E-SATA to SATA interfaces.
- Provides a power switch for connecting your device safely.
- Plug and Play, no jumper pin or ID settings required.
- Supports Windows and Mac system.

Product specification:

Bridge :	USB to IDE	USB to SATA
Interface to PC:	USB 2.0	
Interface to device:	- IDE 40-pin connector - 4-pin power connector	- SATA 7+15pins connector (with power) - SATA 15-pin
Application:	Hard Drive (2.5"/3.5"), CD ROM, CD/RW, DVD ROM, and DVD/RW etc.	Hard Drive (2.5"/3.5") and other SATA devices
Connectors:	- One Mini USB 5-pin to PC. - One 4-pin power connector for IDE device	- One Mini USB 5-pin to PC. - One 15-pin SATA device
Indicator:	- One DC jack (DC12 Volt input; 2.5φplug) for external power adapter - Power switch One power on LED	
Power adapter:	AC input: 100-240VAC, auto-ranging. DC output: 12V/2A,5V/2A (6Pin Mini Din)	
Power source:	12V / 2A ,5V / 2A	
Unit dimension:	67.6(L)*110 (W)* 24.5 (H) mm	
Unit weight:	90g	
OS supports:	Windows: Windows 2000/ XP Macintosh: Mac 10.X or higher	
Storage temperature:	-20℃~60℃	
Operating temperature:	5℃~50℃	
Certificated:	FCC 、 CE	

Package Content:

- Magic Bridge II
- Power adapter (DC 12V, 5V/2A) and power cord
- USB cable (type A to Mini USB)
- 40-44 pin IDE adapter
- IDE 4-pin power cord
- User manual
- Mini IDE converter