

# ComPOS-A1512S

## Dual Display Wireless Touch POS Terminal



<b>System</b>		
Model Name	ComPOS-A1512S	
CPU	Onboard VIA Fanless Eden™ 1.0GHz Processor	
Memory	2 x 240 Pin DIMM socket up to 2GB DDR2 533/400	
Chipset	VIA CX700 Chipset	
Graphics	- CX700 integrated VIA UniChrome™ Pro Integrated Graphics Processor (IGP), - Share with system memory (Up to 128MB)	
Network	10/100/1000 Base-T fast Ethernet 802.11g Wireless LAN (Optional) 56K hardware Modem (Optional)	
Audio	VIA HD Codec VT1708A (Line-out, Mic.)	
Power Supply	DC-in 19V~24V power input	
OS	Windows 2000/XP/XPE, WEPOS	
Key Lock	Front I/O key lock x 1	
LED	Power, LAN, HDD	
<b>Display</b>		
<b>Primary display LCD</b>	15" TFT	
Max. Resolution	1024 x 768	
Brightness	250 cd/m <sup>2</sup>	
Touch Screen	5-wire Analog resistive (ELO, E-Turbo)	
Display Tilting angle	0°~30° for main display	0°~40° for 2nd display
Weight	10.3 Kg	
Dimension	367(W) x 323(D) x 340 (H) mm	

 **HEISEI** Electronics Co., Ltd.

3F, NO. 5, Alley 8, Lane 45, Pao Hsin RD.,  
Hsin-Tien City, Taipei Hsien, Taiwan R.O.C.

Tel: 886-2-2915-2150 Fax: 886-2-2915-2157

http://www.heisei.com.tw/ E-mail: info@heisei.com.tw

Rev : 0.1

<b>2nd display model</b>	
LCD size	12".1 TFT LCD (w/o Touch Screen)
Max. Resolution	1024 x 768
Brightness	220 cd/m <sup>2</sup>
Dimension	323 (W) x 146 (D) x 320 (H) mm
<b>Storage</b>	
HDD	1 x 2.5" S-ATA or IDE Hard Disk drive on pedestal (Optional)
Card reading	1 x Slim type 6 in 1 Card reading drive (Optional)
CF	1 x Compact Flash type I/II socket (Optional) or 1 x DB25 LPT port ( Optional)
<b>I/O Ports</b>	
USB	6 x USB 2.0 (2 x Rear IO, 2x Left side, 2 x On Board Pin Header)
Serial Ports	3 x DB-9 (COM 2, 3, 4) COM 1 is reserved for touch panel +5V/12V Selectable on pin 9
LAN	1 x RJ45 interface
PS/2	2 x PS/2 ports (For keyboard and mouse)
Audio	1 x MIC in / 1 x Line-out
VGA	1 x DB-15 VGA interface for dual display
LPT port	1 x 25 pin ( For printer port)
Modem	2 x RJ11 Phone Jack Modem
Cash Drawer	1 x RJ11 for DC12V cash drawer
<b>Environment</b>	
EMC & Safety	CE, FCC,
Temperature	Operating: 0 ~ 40°C Storage: -20 ~ 60°C
Humidity	10% ~ 90%
<b>Optional Items</b>	
Memory	DDR2 256MB, 512MB, 1GB (DDR2 533, 240Pin)
HDD	40GB (2.5",S-ATA, 5400RPM)
Compact Flash	Built-In Compact Flash Readers
Memory Card reader	Slim type 6 in 1 Memory Card reader
W-LAN	802.11g Wireless LAN module
Modem	56K hardware Modem
MSR	Track 1/2/3 Magnetic Stripe Reader
Customer Display	VFD Customer Display
OS	Windows XP/XPE, WEPOS

The specification is subject to change without any prior notice.

 **HEISEI** Electronics Co., Ltd.

3F, NO. 5, Alley 8, Lane 45, Pao Hsin RD.,  
Hsin-Tien City, Taipei Hsien, Taiwan R.O.C.

Tel: 886-2-2915-2150 Fax: 886-2-2915-2157

http://www.heisei.com.tw/ E-mail: info@heisei.com.tw

Rev : 0.1